



TECHNICAL DATA SHEET

OUTSTANDING FEATURES

- **Widest flow turndown ranges** available in a custody transfer grade turbine flowmeter.
- Designed to be compliant with **API Standard Chapter 5.3**.
- **Rim rotor design** offered in sizes 4"-12" provides for high pulse resolution.
- Bearing types include **self-lubricating, ceramic ball bearings and tungsten carbide sleeve**.
- Optionally available with **multiple pickup coils for redundancy or bi-directional** flow measurement.
- Rotor assembly is **hydrodynamically balanced** and "floats" on fluid cushion to provide extended bearing life.

Custody Transfer Series Rim Flowmeters

The Hoffer **CT Series** turbine flowmeters provide extremely accurate custody transfer grade flow measurement in a rim rotor design. These flowmeters are typically used in liquid petroleum products. This series is recommended for flow applications where high resolution (pulse count) is critical in order to achieve custody transfer grade accuracy.



Note: For bladed design custody transfer flowmeters we offer the API Series.

SIZE SELECTOR CHART FOR "PREMIUM RIMMED" CT SERIES (±.15% LINEARITY)

METER SIZE	NORMAL FLOW RANGE								MAXIMUM EXTENDED FLOW RANGE				PULSES/ GALLON (±5%)	PULSES/ BARREL (±5%)
	MINIMUM LINEAR				MAXIMUM LINEAR									
	GPM	BPH	BPD	M3/HR	GPM	BPH	BPD	M3/HR	GPM	BPH	BPD	M3/HR		
4"	120	172	4128	27	1200	1720	41,280	270	1500	2142	51,408	341	42.3	1776
6"	280	400	9600	63.6	2800	4000	96,000	636	3600	5142	123,008	818	26	1092
8"	520	743	17,832	118.2	5200	7430	178,320	1182	6400	9142	219,008	1454	13.6	571
10"	800	1143	27,432	181.8	8000	11,430	274,320	1818	9800	14,000	336,000	2226	8.68	364
12"	1200	1714	41,136	272.4	12,000	17,140	411,360	2724	15,000	21,428	514,272	3407	5.66	237

Flow ranges and performance specifications are based on a specific gravity of 1.0 and a viscosity of 1.0 centistoke. For performance at other specific gravities and viscosities, consult factory.

RIMMED ROTORS 4"-12"

Materials of Construction: 316 stainless steel (with exceptions noted below).

- Rim Rotor: *Rim* – 316 stainless steel.
Rim Buttons – 430 or 17.4 stainless steel.
- Flanges: 316 stainless steel standard. Optional carbon steel or 304 stainless steel flanges per ASME/ANSI B16.5 are available. Available in ANSI, DIN and ring joint type flanges.
- Bearings: Both tungsten carbide sleeve and ceramic ball bearings types are available.
- Optional NACE compliance per MR0175 available.

GENERAL PERFORMANCE SPECIFICATIONS

- **Linearity:** ±0.15% linearity standard. Improved linearity over reduced flow turndown is optionally available, please consult factory.
- **Repeatability:** ±0.02% at any point throughout the extended flow range.
- **Temperature Range:** -450°F to +450°F, process fluid with standard magnetic pickup coil.
- **Pressure Drop:** 5 PSI at maximum linear flow rate.
- **Output:** 10mV RMS or greater into a 10K ohm load at a minimum flow rate.

A complete line of flowmeter signal conditioners (preamplifiers) and flow computers are available. Consult with the applications group at Hoffer for additional information.

